

RDS / RAPID CEMENT DRYING SYSTEM

이동식 제조 건조 라인(快速烘干活化系統)



특허 시스템 A Patented System (專利 製品)



RDS System의 장점

- NOS / LEAN Project에 아주 적합한 System
- 작은 공간, 낮은 높이, 짧은 폭, 작업 용이, 관리 용이
- 손쉬운 Layout 변경 (Modular System) – 특허 사항
- 다양한 생산 범위 (Sports, Dress, Kids, Boots)
- 완벽한 건조, 개별적 온도 관리 및 정착 강도로 품질 향상
- 환경 친화적 System, 작업 환경 개선 – 배기 덕트 (Option)
- 편리한 작업 동선 (Lasted Upper 넣고 빼기 쉬움) – 특허 사항
- 전력비 절감, Last 절감, Lead Time 감소, 원가 절감
- 작업이 아주 편리한 Shoe Holder – 특허 사항
- 특허 System으로 Know-How 보유 (특허 3가지)
- 많은 납품 실적, 개발 능력 보유, 쉬운 유지 보수, 고객만족...

Features of RDS System

- Most Comfortable System for NOS / LEAN Project
- Small Space, Lower Chamber Height, Easy Motion, Minimum Operation
- Quick Changeover Layout (Modular System) – Patent
- Versatile Product Range (Sports, Dress, Kids, Boots)
- Perfect Drying, Individual Temperature Control, Increased Bonding
- Environment Friendly System – Exhaust Duct (Option)
- Convenient Working Flow – Patent
- Saving Cost (Power, Last, Lead Time... etc)
- Convenient New Type Shoe Holder – Patent
- Made by USM's Experience and Know-How (3 Patents)
- Good Business, Good Development, Easy Maintenance, Customer Satisfaction...



Specification of Chamber

Model	RDS-3 (2 Stations)	RDS-4 (2 Stations)	RDS-5 (2 Stations)
Dimension	750(L) × 1070(W) × 1060(H)mm	1000(L) × 1680(W) × 1160(H)mm	1000(L) × 1680(W) × 1300(H)mm
Power	220/380V, 3Ph, 50/60Hz, 6Kw	16Kw(Double)	22Kw(Double)

